Homax®

Ceiling Texture

Textura para techo

Textura rugoso

PRO GRADE

POPCORN

8 sq. ft.

Hasta 6,50 m²

FAST, PROFESSIONAL RESULTS

Controlled Application

Delivers an Invisible Repair™

Matches Commercial Popcorn Textures

RESULTADOS RÁPIDOS Y PROFESIONALES
Aplicación controlada
Proporciona una reparación invisible
Iguala a las texturas rugosas comerciales

DANGER! FLAMMABLE VAPOR. CONTENTS UNDER PRESSURE. CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION.
Read other cautions on side/back panel before using.

¡PELIGRO! VAPOR INFLAMABLE. CONTENIDO BAJO PRESIÓN. PROVOCA IRRITACIÓN OCULAR, EN LA PIEL Y EN LAS VÍAS RESPIRATORIAS.
Lea otras precauciones en el panel posterior y lateral antes de usar.

NET WT 14 OZ (397 g)

WATER BASED

BASE DE AGUA

Homax® Pro Grade Ceiling Texture delivers an invisible repair™ by replicating polystyrene, perlite or other popcorn type ceiling textures. Ideal for patching, this professional texture tool makes popcorn repairs fast and easy, providing a portable and convenient alternative to a hopper gun.

Watch a How-to Video at homaxproducts.com or scan this code to watch now!

Ver el Video Instructivo en homaxproducts.com o explore con su Smartphone para verlo ahora.

PROTECT CARPET, FURNITURE AND WALLS FROM OVERSPRAY.

- Water-based, use warm water for clean up.
- Sprays best between 68° F and 72° F.
- Wear eye protection.

DIRECTIONS FOR USE: MAKE ANY NECESSARY CEILING REPAIRS BEFORE APPLYING. PRIME/SEAL AREA WHITE BEFORE APPLYING TEXTURE.

1. **SHAKE CAN** vigorously for one full minute after you hear ball rattle in can and periodically during use. Ideally last shake motion should be downward to ensure material inside moves to bottom of can.
2. **TO UNLOCK TRIGGER,** turn RED safety lock counterclockwise.
3. **SPRAY** can **UPRIGHT** 20"- 30" away from ceiling and spray **CONTINUOUSLY,** sweeping across repair in a rapid, continuous motion and feathering texture into surrounding area.
4. **AFTER USE AND TO STORE,** turn can upside down and spray until texture is cleared. Return safety to locked position. Remove any texture build up from tip/nozzle.

DRY TIME: Allow texture to dry 24 hours.


TIPS:

Painting is not required, but if desired to match surrounding area, apply lightly with paint brush or foam pad.

For a finer chip size, hold can further away from ceiling and spray.

For a coarser chip size, partially squeeze trigger, or hold can closer to ceiling when spraying.

For a heavier texture application, apply first coat, allow to dry, then apply second coat to build texture as desired.



PROTEJA LAS ALFOMBRAS, MUEBLES Y PAREDES DEL EXCESO DE ROCIADO.

- A base de agua, utilice agua tibia para la limpieza.
- Se rocía mejor entre 20 °C y 22,2 °C.
- Use lentes de protección.

INSTRUCCIONES DE USO: ANTES DE LA APLICACIÓN, REPARE EL TECHO SEGÚN SEA NECESARIO. APLIQUE PINTURA BASE O SELLE EL ÁREA DE BLANCO ANTES DE APLICAR LA TEXTURA.

1. **AGITE LA LATA** vigorosamente durante un minuto completo después de escuchar el ruido de la bola de mezclar en la lata y de forma periódica durante el uso. De preferencia, cuando agite por última vez hágalo hacia abajo para asegurar que el material en el interior se desplace hacia el fondo de la lata.
2. **PARA DESBLOQUEAR EL GATILLO,** gire el seguro ROJO en dirección contraria a las manecillas del reloj.
3. **ROCÍE** la lata **DE FORMA VERTICAL** a una distancia entre 51 cm y 76 cm del techo y rocíe **DE FORMA CONTINUA** barriendo con un movimiento rápido y continuo la reparación y alisando la textura en el área circundante.
4. **DESPUÉS DE USAR Y PARA ALMACENAR EL PRODUCTO,** coloque la lata en posición invertida y rocíe hasta que no quede rastro de la textura. Vuelva a colocar el seguro. Retire la textura acumulada en la punta/boquilla.

TIEMPO DE SECADO: Deje que la textura seque por 24 horas.

CONSEJOS:

No se requiere pintar, pero si desea combinar con el área circundante, aplique ligeramente con una brocha o con una almohadilla de espuma.

Si desea una textura más fina, sostenga la lata a mayor distancia del techo y rocíe.

Si desea una textura más gruesa, presione el gatillo parcialmente o sostenga la lata a menor distancia del techo al momento de rociar.

Si desea una textura más densa, aplique una primera capa, deje secar y aplique una segunda capa hasta lograr la textura deseada.

DANGER! Contains Calcium Carbonate, Talc, Magnesium Carbonate, Hexylene Glycol, Quartz, Sodium Nitrite and Dimethyl Ether (propellant). Vapors may catch fire. Keep away from heat, sparks and flame. Extinguish all flames and sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Store upright in a cool, dry place. Avoid prolonged exposure to sunlight and other heat sources that may cause bursting. Do not puncture, incinerate, burn or store above 120°F. Use with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with eyes and skin. Wear safety glasses or goggles. Wash hands after using. **FIRST AID:** For eye contact, flush thoroughly with water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. If inhaled, remove person to fresh air. If breathing does not improve, get medical attention.

KEEP OUT OF THE REACH OF CHILDREN. WARNING: This product contains a chemical known to the State of California to cause cancer. **WARNING:** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. **WARNING:** If your ceiling texture was applied prior to 1979, DO NOT attempt to remove it without having it tested for asbestos content. Contact your local EPA office or log on to www.epa.gov/asbestos for information.

Flat Paint Product VOC < 60% MIR <1.20

This product is covered by one or more U.S. Patents.

Homax® A Premier Brand of The Homax Group, Inc.
Bellingham WA 98227
www.homaxproducts.com
800-729-9029

MADE IN USA

4575_22915 050213 DOT 2Q

0 41072 04575 9